

Weber® Packaging Solutions, Inc.

711 W. Algonquin Road · Arlington Heights, IL 60005-4457
Phone 847/364-8500

Product Information

Pressure-Sensitive Label Materials

Ultraplate (White, Silver, Clear)

DESCRIPTION	<ul style="list-style-type: none">Gloss polyester film designed for durable nameplate applications												
FACESHEET	<ul style="list-style-type: none">2-mil gloss polyesterDesigned to accept thermal-transfer imprintingUltimate abrasion resistance; Remains stable outdoorsTensile (MD/CD): 21,300 psi / 28,400 psi												
ADHESIVE	<ul style="list-style-type: none">High performance solvent acrylicAdhesive caliper: 0.009 milHigh degree of initial tack and ultimate bond strengthAdheres to aluminum, painted metal, steel, plastic, polypropylene, polyethylene, polyvinyl chlorideApplication temperature (min.): +50°FUse temperature range: -40°F to 302°F												
LINER	<ul style="list-style-type: none">3.2 mil bleached, super-calendered paperBasis weight: 50 lbs. per ream (500 - 24" x 36")												
VARIABLE PRINTING	<ul style="list-style-type: none">Compatible with Zebra, Sato, and Datamax thermal-transfer printersCompatible with automatic applying equipmentNot compatible with dot matrix printingNot compatible with laser printingFor thermal-transfer imprinting utilize the Ultraplate II ribbon.												
APPLICATIONS	<ul style="list-style-type: none">Nameplates • Serial plates • Rating plates • Bin/shelf identification • Property asset management												
UL/CSA CERTIFICATION	<table><thead><tr><th><u>Printer Technology</u></th><th><u>Required Components</u></th><th><u>File Number</u></th></tr></thead><tbody><tr><td>• Zebra, Sato & Datamax printers</td><td>• Ultraplate II ribbon</td><td>• UL-MH16091</td></tr><tr><td>• All print/apply</td><td>• Ultraplate Select label</td><td>• CUL-MH16091</td></tr><tr><td></td><td>• Zebra, Sato & Datamax printers</td><td></td></tr></tbody></table>	<u>Printer Technology</u>	<u>Required Components</u>	<u>File Number</u>	• Zebra, Sato & Datamax printers	• Ultraplate II ribbon	• UL-MH16091	• All print/apply	• Ultraplate Select label	• CUL-MH16091		• Zebra, Sato & Datamax printers	
<u>Printer Technology</u>	<u>Required Components</u>	<u>File Number</u>											
• Zebra, Sato & Datamax printers	• Ultraplate II ribbon	• UL-MH16091											
• All print/apply	• Ultraplate Select label	• CUL-MH16091											
	• Zebra, Sato & Datamax printers												
SHELF LIFE	<ul style="list-style-type: none">1 year at 72°F and 50% R.H.												

REV DATE 01: 2/07/13

ALL MEASUREMENTS ARE +/- 10%
IT IS THE CUSTOMER'S RESPONSIBILITY TO DETERMINE THE SUITABILITY OF THIS
PRODUCT FOR THEIR PARTICULAR APPLICATION